AMENDMENTS TO THE SPECIFICATION

Please replace paragraph 0022 of the application, appearing at page 8 line 3 to page 9 line 5 of the specification as filed, with the following paragraph:

The leg 24a of the body 22 has a plurality of receptacles 28a-28e inherently built therein at different, spaced heights from the bottom 12 of the concrete form 10 when the multi-level chair 20 is placed on the bottom 12 of the concrete form 10. Similarly, the leg 24b of the body 22 has a plurality of receptacles 28f-28k inherently built therein at different heights from the bottom 12 of the concrete form 10 when the multi-level chair 20 is placed on the bottom 12 of the concrete form 10. The receptacles 28a-28k are each located at a different height from the bottom 12 of the concrete form 10 when the multi-level chair 20 is placed on the bottom 12 of the concrete form 10. More specifically, the receptacles 28a-28e of the multi-level chair 20 are at staggered heights relative to the receptacles 28f-28k. For example, when the multi-level chair 20 is placed on the bottom 12 of the concrete form 10 receptacle 28a is 0.75 inches above bottom 12 of the concrete form 10; receptacle 28f is 1.00 inches above the bottom 12 of the concrete form 10; receptacle 28b is 1.25 inches above the bottom 12 of the concrete form 10; receptacle 28g is 1.25 inches above the bottom 12 of the concrete form 10, etc. Therefore, none of the receptacles are at identical heights when the multi-level chair 20 is placed on the bottom 12 of the concrete form 10. The receptacles 28a-28k are spaced a fixed distance from each other; 0.25 inches in the example described above. Although, in the example described the receptacles are spaced from each other 0.25 inches, this distance may be any desired distance. Although five receptacles 28a-28e are illustrated and described built into the leg 24a and six receptacles 28f-28k are illustrated and described built into the leg 24b, any a

<u>lesser or greater</u> number of receptacles may be formed in either leg without departing from the spirit of the invention of this application.

Please replace paragraph 0035 of the application, appearing at page 13 lines 11-23 of the specification as filed, with the following paragraph:

[0035] Each leg 24c of the body 22c has a plurality of receptacles 62 inherently built therein at different, spaced heights from the bottom 12 of the concrete form 10 when the multi-level chair 20c is placed on the bottom 12 of the concrete form 10. Again, the receptacles 62 are each located at a different height from the bottom 12 of the concrete form 10 when the multi-level chair 20c is placed on the bottom 12 of the concrete form 10. the bottom 12 of the concrete form 10, etc. Therefore, none of the receptacles are at identical heights when the multi-level chair 20 is placed on the bottom 12 of the concrete form 10. The receptacles 62 are preferably spaced a fixed distance from each other. Although four receptacles 62 are illustrated and described built into each leg 24c, any a lesser or greater number of receptacles may be formed in either leg without departing from the spirit of the invention of this application.